

## CLAIMS

We claim:

1           1.     In a base station wideband transceiver capable of operating in a  
2 wireless cellular communications system that communicates with mobile  
3 subscribers, a method for equalization in transmit and receive levels, comprising the  
4 steps of:

5           assigning a plurality of transmit and receive carrier frequencies to the base  
6 station wideband transceiver; and

7           flattening the power in the plurality of transmit and receive carrier  
8 frequencies in the base station wideband transceiver using software amplitude pre-  
9 distortion.

10           2.    The method according to claim 1, wherein the step of flattening  
11 further comprises the step of discretely flattening the power in each of the plurality  
12 of transmit and receive carrier frequencies to provide one nominal output level for a  
13 predetermined input level for each transmitted or received RF carrier.

14           3.    The method according to claim 1, wherein the step of flattening using  
15 software amplitude pre-distortion further comprises the step of applying a series of  
16 flattening coefficients to the receive and transmit signals to compensate for at least  
17 the effects of a digital-to-analog converter in the base station wideband transceiver.

{P1001617;4}

1           4.     The method according to claim 1, wherein the step of flattening using  
2 software amplitude pre-distortion further comprises the step of compensating for  
3 narrowband IF ripple and filter roll-off distortion.

1           5.     The method according to claim 4, wherein the step of flattening using  
2 software amplitude pre-distortion further comprises the step of compensating for  
3 wideband RF ripple and filter roll-off distortion.

1           6.     The method of claim 1, wherein the method further comprises the  
2 step of making narrowband IF channel measurements using an automated  
3 broadband radio frequency transceiver test (ABRFTT) to determine a set of  
4 coefficients for each narrowband IF channel.

1           7.     The method of claim 6, wherein the ABRFTT further comprises the  
2 step of making wideband RF channel measurements that step through the  
3 wideband bandwidth to determine a set of coefficients for the wideband RF  
4 channel.

1           8.     The method of claim 7, wherein the ABRFTT creates 25 narrowband  
2 coefficients for a 5 MHz IF bandwidth and 300 wideband coefficients for a 60 MHz  
3 RF bandwidth having 200 kHz channels.

{P1001617;4}

1           9.     The method of claim 7, wherein the method further comprises the  
2     step of storing the coefficients in a memory in the base station wideband  
3     transceiver enabling the interchangeability of base station wideband transceivers  
4     within the wireless cellular communication system.

1           10.  The method of claim 9, wherein the method further comprises the steps  
2     of storing the wideband coefficients and the narrowband coefficients in a look-up  
3     table in memory within the base station wideband transceiver.

1           11.  The method of claim 7, wherein the method further comprises the step  
2     of setting a corresponding gain for each individual radio frequency based on the  
3     narrowband IF and wideband RF coefficients determined from the automated  
4     broadband radio transceiver test.

1           12.  A broadband radio frequency base transceiver capable of receiving and  
2     transmitting simultaneously on multiple frequencies, comprising:

3                 a receiver coupled to an plurality of analog-to-digital converters,  
4     wherein the analog-to-digital converters provide a plurality of digitized signals;  
5                 a transmitter coupled to a digital-to-analog converter, wherein the  
6     digital-to-analog converter produces an analog signal from a multi-channel digital  
7     combiner; and

{P1001617;4}

8 at least one digital signal processor programmed to discretely flatten  
9 the power in each of the plurality of transmit and receive carrier frequencies using  
10 software amplitude pre-distortion.

1 13. The broadband radio frequency base station transceiver of claim 12,  
2 wherein the receiver has a receiver digital signal processor that applies a series of  
3 flattening coefficients to the receive signal to compensate for the effects of the  
4 wideband RF and narrowband IF ripple and filter roll-off distortion.

1 14. The broadband radio frequency base transceiver of claim 12, wherein  
2 the transmitter has a transmitter digital signal processor that applies a series of  
3 flattening coefficients to compensate for the effects of the digital-to-analog  
4 converter.

1 15. The broadband radio frequency base transceiver of claim 12, wherein  
2 the transceiver further comprises a transceiver microprocessor module having  
3 memory for storing a plurality of wideband RF and narrowband IF coefficients for  
4 setting a corresponding gain for each individual frequency.

1 16. The broadband radio frequency base transceiver of claim 12, wherein  
2 the transceiver is a translating repeater.

{P1001617;4}

1 17. A wireless cellular communications system with improved equalization in  
2 transmit and receive levels, comprises:

3 a plurality of wideband transceivers communicating with mobile  
4 subscribers, wherein a plurality of transmit and receive carrier radio frequencies are  
5 assigned to the plurality of wideband transceivers, each of the wideband  
6 transceivers comprises:

7 a receiver coupled to an plurality of analog-to-digital converters,  
8 wherein the analog-to-digital converters provide a plurality of digitized signals to a  
9 corresponding plurality of digital channelizers;

10 a transmitter coupled to a digital-to-analog converter, wherein the  
11 digital-to-analog converter receives an analog signal from a multi-channel digital  
12 combiner;

13 a first digital signal processor programmed to discretely flatten the  
14 power in each of the plurality of receive carrier frequencies using software  
15 amplitude pre-distortion; and

16 a second digital signal processor programmed to discretely flatten the  
17 power in each of the plurality of transmit carrier frequencies using software  
18 amplitude pre-distortion.

1 18. The wireless communication system of claim 17, wherein each of the  
2 plurality of wideband base transceivers is a translating repeater.

{P1001617;4}